according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Page: 1

Compilation date: 18.02.2011

Revision date: 30.08.2018

Revision No: 6.21

Section 1: Identification of the substance/mixture and of the company/undertaking

*1.1. Product identifier

Product name: Cleaner tab for SCC and CMP models with automatic cleaning

Art.-No. 56.00.207, 56.00.212, 56.00.221

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Cleaner for professional users

*1.3. Details of the supplier of the safety data sheet

Company name: LechMetall GmbH

Siegfried-Meister-Straße 1 86899 Landsberg am Lech

Germany

Tel: +49 8191 327-2563
Fax: +49 8191 327-72 2563
Email: reinigung@lechmetall.de

1.4. Emergency telephone number

Emergency tel: +49 89 19 240 NPIS: 0870 600 62666

Giftnotruf München 'Klinikum rechts der Isar' National poison information service (UK)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1A: H314

Most important adverse effects: Causes severe skin burns and eye damage.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

Hazard pictograms: GHS05: Corrosion



Signal words: Danger

Hazard components for labelling: sodium hydroxide, disodium metasilicate, fatty alcohol ethoxylate

Precautionary statements: P102: Keep out of reach of children.

P101: If medical advice is needed, have product container or label at hand.

P280: Wear protective gloves/eye protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water.



CLEANER TAB FOR SCC and CMP

Page: 2

10-<20%

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P310: Immediately call a POISON CENTER / doctor.

P501: Dispose of contents to problem waste.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

6834-92-0

3.2. Mixtures

229-912-9

Hazardous ingredients:

SODIUM HYDROXIDE - REACH registered number(s): 01-2119457892-27-0000

EINECS	CAS	SCL	CLP Classification	Percent	
215-185-5	1310-73-2	-	Skin Corr. 1A: H314	>20%	
DISODIUM METASILICATE - REACH registered number(s): 01-2119449811-37-0000					

SODIUM CARBONATE - REACH registered number(s): 01-2119485498-19-0000

207-838-8	497-19-8	-	Eye Irrit. 2: H319	10-20%	

Skin Corr. 1B: H314; STOT SE 3: H335

FATTY ALCOHOL ALKOXYLATE - REACH registered number(s): 02-2119548491-37-0000

-	111190-40-0	-	Eye Dam. 1: H318; Aquatic Acute 1:	1-<2.5%	
			H400; Aquatic Chronic 2: H411		

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the

affected skin with running water for 10 minutes or longer if substance is still on skin.

Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist

examination.

Ingestion: Wash out mouth with water. If conscious, give half a litre of water to drink immediately. Do

not induce vomiting. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Irritation or pain may occur at the site of contact. Severe burns may occur.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Nausea and stomach pain may occur.

Inhalation: Not applicable.

CLEANER TAB FOR SCC and CMP

Page: 3

Delayed / immediate effects: Immediate effects can be expected after long-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with

skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Wash the spillage site with large amounts of water. Refer to section 13 of SDS for suitable

method of disposal.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Storage class: 8B (Non-

combustible corrosive substances)

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

CLEANER TAB FOR SCC and CMP

Page: 4

8.1. Control parameters

Hazardous ingredients:

SODIUM HYDROXIDE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	2 mg/m ³	-	-

*DNEL/PNEC Values

Hazardous ingredients:

SODIUM HYDROXIDE

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation (repeated dose)	1,0 mg/m ³	Workers	Local
DNEL	Dermal	2%	Workers	Local

DISODIUM METASILICATE

Туре	Exposure	Value	Population	Effect
DNEL	Dermal	1,49 mg/kg	Workers	Systemic
DNEL	Inhalation	6,22 mg/m ³	Workers	Systemic
DNEL	Dermal	0,74 mg/kg	Population	Systemic
DNEL	Inhalation	1,55 mg/m ³	Population	Systemic
DNEL	Oral	0,74 mg/kg	Population	Systemic
PNEC	Fresh water	7,5 mg/l	-	-

SODIUM CARBONATE

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation	10 mg/m ³	Workers	_

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Gloves (alkali-resistant). Nitrile gloves. Breakthrough time of the glove material < 1 hour.

Suitable material NR (natural rubber), CR (polychloroprene) or NBR (nitrile rubber).

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Not applicable.

Environmental: No special requirement.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Solid
Colour: White

CLEANER TAB FOR SCC and CMP

Page: 5

Odour: Characteristic odour

Evaporation rate: Not applicable.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Viscosity: Not applicable.

Boiling point/range°C: Not applicable. Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: Not applicable. Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: Not applicable.

Relative density: 1100 g/l **pH**: 12.7 (1%)

VOC g/l: <3%

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Humidity.

10.5. Incompatible materials

Materials to avoid: Acids. Metals.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes. Contact with acids liberates toxic gas.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

CLEANER TAB FOR SCC and CMP

Page: 6

SODIUM HYDROXIDE

IPR	MUS	LD50	40	mg/kg
ORL	RBT	LDLO	500	mg/kg

DISODIUM METASILICATE

ORL	MUS	LD50	770	mg/kg
ORL	RAT	LD50	1153	mg/kg

SODIUM CARBONATE

ORL	MUS	LD50	6600	mg/kg
ORL	RAT	LD50	4090	mg/kg
SCU	MUS	LD50	2210	mg/kg

FATTY ALCOHOL ALKOXYLATE

ORAL	RAT	LD50	3180	ma/ka
ONAL	1041	LD30	3100	ilig/ kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: Irritation or pain may occur at the site of contact. Severe burns may occur.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Nausea and stomach pain may occur.

Inhalation: Not applicable.

Delayed / immediate effects: Immediate effects can be expected after long-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

SODIUM HYDROXIDE

Daphnia magna	24H EC50	76	mg/l
Gambusia affinis	96H LC50	125	mg/l

SODIUM CARBONATE

Freshwater Invertebrates	48H EC50	200-227	mg/l
Lepomis macrochirus	96H LC50	300	mg/l

CLEANER TAB FOR SCC and CMP

Page: 7

FATTY ALCOHOL ALKOXYLATE

Aquatic Invertebrates	48H EC50	0.1-1	mg/l
Leuciscus idus	96H LC50	0.1-1	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Soluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 20 01 29

Disposal of packaging: May be reused following decontamination.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3262

14.2. UN proper shipping name

Shipping name: CORROSIVE SOLID, BASIC, INORGANIC, N.O.S.

(SODIUM HYDROXIDE; DISODIUM METASILICATE; Limited Quantity: 1kg)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

CLEANER TAB FOR SCC and CMP

Page: 8

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E
Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

*Specific regulations: Ingredients according to Regulation (EC) No 648/2004: 15-30% phosphates,

<5% polycarboxylates, non-ionic surfactants.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the

supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU)

2015/830

* indicates text in the SDS which has changed since the last revision. Data references: Safety data sheets from our raw material suppliers

Classification for mixtures and used evaluation method according to Article 9 of

regulation (EC) 1272/2008 [CLP]:

Calculation method

Phrases used in s.2 and s.3: H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage.H319: Causes serious eye irritation.H335: May cause respiratory irritation.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.